

# **Santolubes LLC**

Findett, Santotrac, Santovac, Santolubes, and Synergy  
PO Box 6740  
Spartanburg, SC  
29304

## **Safety Data Sheet**

Page 1 of 8

---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: **SANTOLUBES® 150J Traction Lubricant**

Company Name: Santolubes Japan GK  
Chemical Family: Synthetic Hydrocarbon  
Chemical Name: CAS NO:38970-72-8  
1,1'-(1,1,3-trimethylpropane-1,3-diyl)bis(cyclohexane)

CHEMICAL EMERGENCY: Phone: + 81-776-43-1456 Fax: + 81-776-43-1466

---

### 2. HAZARDS IDENTIFICATION

---

#### GHS CLASSIFICATION OF THE SUBSTANCE OR MIXTURE :

This material is not classified for any hazards of GHS.

#### PHYSICAL HAZARDS

Explosives	: classification not possible.
Flammable gases	: Not applicable.
Flammable aerosols	: Classification not possible.
Oxidizing gases	: Not applicable
Gases under pressure	: Not applicable.
Flammable liquids	: Not applicable.
Flammable solids	: Not classified.
Self-reactive substances and mixture	: Classification not possible.
Pyrophoric liquids	: Classification not possible.
Pyrophoric solids	: Not applicable.

---

**Santolubes LLC MATERIAL SAFETY DATA SHEET****Page 2 of 8**

SANTOLUBES® 150J

Self-heating substances and mixtures : Classification not possible.

Substances and mixtures, which in contact with water, emit flammable gases : Classification not possible.

Oxidizing liquids : Classification not possible.

Oxidizing solids : Not applicable.

Organic peroxides : Classification not possible.

Corrosive to metals : Classification not possible.

**HEALTH HAZARDS**

Acute toxicity: ora1 : Not classified.

Acute toxicity: skin : Not classified.

Acute toxicity: inhalation (gas) : Not applicable.

Acute toxicity: inhalation (vapor) : Classification not possible.

Acute toxicity: inhalation (dust) : Not applicable.

Acute toxicity: inhalation (mist) : Classification not possible.

Skin corrosion/irritation : Category 3

Serious eye damage/eye irritation : Category 2B

Respiratory sensitization : Classification not possible.

Skin sensitization : Classification not possible.

Germ cell mutagenicity : Classification not possible.

SANTOLUBES® 150J

possible.

Carcinogenicity : Classification not possible.

Toxic to reproduction : Classification not possible.

Specific target organ toxicity (single exposure) :Classification not possible.

Specific target organ toxicity (repeated exposure) : Classification not possible.

Aspiration hazard :Classification not Possible.

**ENVIRONMENTAL HAZARDS**

Hazardous to the aquatic environment (acute) : Not classified

Hazardous to the aquatic environment ( chronic) :Classification not possible

**GHS LABEL ELEMENTS :**

PICTOGRAMS : Not required

SIGNAL WORD : Warning

HAZARD STATEMENTS : Causes minor skin irritation and may cause eye and respiratory irritation.

Skin irritation-minor Category 3 H316

Eye irritation-minor Category 2B H320

SANTOLUBES® 150J

**PRECAUTIONARY STATEMENTS**

Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact.

Avoid breathing dust/fume/gas/mist/vapors/spray.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Prevention :**

Obtain special instructions before use, and DO NOT handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use only outdoors or in a well-ventilated area and DO NOT breathe dust mist/vapor.

Use personal protective equipment; protective helmet/eye protection/face protection/respirator/protective

gloves/protective clothing/safety shoes as required.

Wash hands, face, and other necessary parts thoroughly, and gargle after handling.

Avoid release to the environment.

**Response :**

IF exposed or concerned, or if you feel unwell : Get medical advice/ attention.

**Storage :**

Avoid direct sunlight, open flame, ignition sources. Store in well ventilated area..

**Disposal :**

Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not reuse the container for any other purpose. Dispose of in accordance with applicable laws and regulations.

**OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION :**

None. Specific hazard for usual industrial or commercial handling.

Polymers are expected to be physiologically inert and not to cause any acute toxicological effects.

SANTOLUBES® 150J

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

Synthetic Hydrocarbon: 70 –99%

---

**4. HAZARDS IDENTIFICATION**

---

Primary routes of exposure:

Eye contact: Material can cause slight to moderate irritation.

Skin contact: Slight to moderate skin irritation is expected.

---

**5. FIRST AID MEASURES**

---

EYES: immediately flush with plenty of water for at least 15 minutes. Call a physician.

SKIN: wipe off excess and wash with soap and plenty of water. Remove contaminated clothing. Wash clothing before reuse.

---

**6. FIRE FIGHTING MEASURES**

---

Flash Point:291.2°F (COC)

Extinguishing Media: Water spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent.

Special Fire Fighting Procedures: Fire fighters or others likely to be exposed to products of combustion should wear full protective clothing including self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

Unusual Fire and Explosion Hazards: Products of decomposition include hazardous carbon monoxide, carbon dioxide, and hydrocarbons.

---

**7. ACCIDENTAL RELEASE MEASURES**

---

IN CASE OF SPILL OR LEAK: Absorb with a suitable media such as sawdust, clay or filtercel.

---

**8. HANDLING AND STORAGE**

---

SANTOLUBES® 150J lubricant is stable under ordinary handling and storage conditions.

---

**9. EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

Eye Protection: Santolubes® 150J Traction Lubricant causes only slight eye irritation. No special protection required. Avoid eye contact as good industrial practice.

SANTOLUBES® 150J

**Skin Protection:** Wear appropriate protective gloves that provide a barrier and protective clothing to prevent skin contact. Consult glove manufacturer to determine appropriate type glove for given application. Wear face shield and apron when splashing is likely. Wash contaminated skin promptly. Launder contaminated clothing and clean protective equipment before reuse. Wash thoroughly after handling.

**Respiratory Protection:** Avoid breathing vapor or mist. Use NIOSH/MSHA approved equipment. The respirator use limitations specified by NIOSH/MSHA or the manufacturer must be observed. High airborne concentrations may require use of self-contained breathing apparatus or supplied air respirator. Respiratory protection programs must be in compliance with 29 CFR 1910.134.

**Ventilation:** Provide ventilation to minimize exposure. Use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

---

## 10. PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance:	Orange liquid
Density @ 25°C:	0.88 – 0.92 g/cc
Viscosity @ 100°F:	135 – 165 centistokes
Solubility in Water:	Very low

---

## 11. STABILITY AND REACTIVITY

---

**Stability:** Santolubes® 150J lubricant is stable under ordinary handling and storage conditions.

**Materials to Avoid:** Exposure to highly oxidizing materials should be avoided.

**Hazardous Decomposition Products:** No uniquely hazardous decomposition products are expected. If the product is burned carbon dioxide, carbon monoxide, low molecular weight hydrocarbons, soot, and smoke can be produced.

**Hazardous Polymerization:** Will not occur.

---

## 12. TOXICOLOGICAL INFORMATION

---

### Toxicological Data

Findett has not conducted acute toxicity studies with Santolubes® 150J. However, the following acute data were developed on the synthetic hydrocarbon base fluid, and are considered to be representative of Santolubes® 150J.

Oral LD50 (Rat): Greater than 15,800 mg/kg, Practically Nontoxic

Dermal LD50 (Rabbit): Greater than 7,940 mg/kg, Practically Nontoxic

---

**Santolubes LLC MATERIAL SAFETY DATA SHEET**

Page 7 of 8

SANTOLUBES® 150J

Eye Irritation (Rabbit, 24-hr): 3.5 on a scale of 110.0, Slightly Irritating

Skin Irritation (Rabbit, 24-hr): 0.0 on a scale of 8.0, Nonirritating

Vapor Inhalation (Rat): Rats were exposed to a stream of air passed through the lubricant and led directly into the experimental chamber. Due to its low volatility, there was essentially no vaporization of the test material and the animals survived both the 6-hour exposure and subsequent 10-day observation periods without observable effects.

---

**13. ECOLOGICAL INFORMATION**

---

Santolubes® 150J had a primary degradation rate of 7% to 21% in a 24-hour semi-continuous activated sludge test (SCAS). Biodegradability of this material was classified as slow to resistant.

Oral LD50 Mallard Duck: Greater than 4,640 mg/kg, Practically Nontoxic

Oral LD50 Bobwhite Quail: Greater than 4,640 mg/kg, Practically Nontoxic

96-hr LC50 Fathead Minnow: Greater than 1,000 mg/l, Practically Nontoxic

---

**14. DISPOSAL CONSIDERATIONS**

---

This material when discarded is not a hazardous waste as defined by the Resource, Conservation and Recovery Act (RCRA), 40 CFR 261. Dispose of in accordance with all federal, state and local environmental regulations. Recommended method of disposal is by high temperature incineration in a RCRA approved TSDF.

---

**15. TRANSPORT INFORMATION**

---

Hazard Class:

This material is not classified as a hazardous material by the U.S. Department of Transportation (DOT) nor by the International Air Transport Association (IATA).

---

**16. REGULATORY INFORMATION**

---

SARA Hazard Notification Hazard Categories Under Criteria of SARA Title III Rules (40 CFR Part 370): Immediate

Section 313 Toxic Chemical(s): Not Applicable

---

**17. OTHER INFORMATION**

---

---

NOTICE: Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, Santolubes LLC makes no representations as to the

---

---

**Santolubes LLC MATERIAL SAFETY DATA SHEET****Page 8 of 8**

SANTOLUBES® 150J

---

completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving same will make their own determinations as to its suitability for their purposes prior to use. In no event will Santolubes LLC be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OR MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

---

DATE: 1/22/2024

(The DISTRIBUTOR)  
Limited Liability Company  
Of Element Technical

Kumonmyou, 80-141-16 Tsuruga shi  
Fukui 914-0133 JAPAN +81-77021-3017 fax +81-770-37-5019